

FUNDUS CAMERA









FUNDUS CAMERA

Features

- One touch images acquisition
- Fast and accurate autofocus
- Non-mydriatic and auto exposure
- Photography fundus and Auto fluorescence (FAF)
- 10.1 inch TFT touch screen
- Dual-camera system eyes of the device
- Soft lighting advanced optical technology
- Non-mydriatic design-Minimum pupil size of 3.3mm
- 135°wide field 9 position mosaic device
- Quality components Step motor
- Multifunctional software system





Specifications

Image acquisition system

• Acuisition modes: Non-mydriatic/mydriatic photography anterior segment

photography fundus ,fluorescence angiography (FFA

optional). Auto fluorescence (FAF optional)

• Field of view: 50°

• Minimum pupil size: ≥3.3mm

• Focus modes: Auto /manual

• Operation: Auto

Image acquisition time: Within 10 secondsImage resolution: 18 megapixels

Working distance: 35mmDiopter Compensation: ±25D

• Fixation: External fixation/internal fixation

• DICOM 3.0: YES

• Dimensions: 380mm (L)x 550mm(W)X475mm(H)

• Weight: 26.5kg

• Power supply: 100-240V 50/60Hz

Accessories

- External Eye Fixation Lamp
- Hard-shell Travel Case
- Wheelchair Accessible Table
- Laptop Computer/Monitor





MUSEUM HILL CENTRE, MUSEUM ROAD P.O. BOX 75534 00200 NAIROBI, KENYA

Tel: 0720 714 337 Email: info@medsurgehealth.co.ke Web: www.medsurgehealth.co.ke

