LED AUTO CHART PROJECTOR

- Contract











LED Auto Chart Projector

Description

Led lamp with two kinds color light, warm and cold.

Auto chart projector is a precision optical instrument for accurate refraction. It provides 30 different charts and 35 masks, with programmable remote control. Duochrome test charts to check single and binocular vision, and polarized test charts to check binocular vision and ocular muscle imbalance. It is LED light.





ACP-1500A	C 0.05	0CO 0.1 0 0 0 0.16	0000002 0000003 0000004	0000005 0000065 0000067	00000008 0000009 0000010	0000012 0000015 0000020
50 05 34 43 280 012	EM3WE0.2 WEM3M0.3 E3WME0.4	3 E W M W 0.5 W 3 M E 3 0.6 M W E 3 M 0.7	3 MEWE 0.8 MW3 EM 0.9 WEM3 E 1.0	3WEMW12 E3WEM1.5 WEMW32.0	∃ШП о.1 ПЕШо.16	5436703 6829404 3286505
2856304 9452710 9342707 6834912 5698408 5928315	458 º.1 293 º2	₩₩¥ 02 \$ \$ \$ 03	\$ % \$ + \$ 0.4 \$ - \$ % + 0.5 % \$ + \$ \$ 0.6	**************************************	*	0000 0000 0000
	•	0	8	-		•
ACP-1500B	E ##	Ш 📽	END 200 SLH 159 SLH 159	HBDVA 100 PHTCK 월	VLNEB 70 DAOFP 60 EGDN3 50	FZBOT 12 OFLOV 80 APEOH 25
TZVFC 20 EHPNL EVOTL 20 TEGAK VEOTB 10 HSFZN 10 HSFZN 10 HSFZN	ШЕП ³³ МЭШ ³³	WEMBW 40 EMBWB 21 MBWEM 40 NBWEM 40	EW3MW 18 W3ME3 19 MEW3M 19	3WEMW 26 WEM3E 20 EM3W3 16 EM3W3 46	852 ³⁰⁰ 643 ¹⁰⁰	29387 ¹⁰⁰ 75482 ⁵⁰ 38549 ⁷⁹
69832 ⁴³ 38297 ⁴⁰ 42576 ⁴⁰ / ₁₂ 53948 ¹⁰ / ₁₅ 93754 ⁴⁰ / ₁₂ 82573 ⁴⁰ / ₄	♥ **	}; ₹ } }; \$	トカミート (18 ミートカー 112 ーミカトカ 112 ーミカトカ 112	•	10 9 9 7 4 7 4 8	*
•••	0	PTTP 2NN2 DAAD	ағға <u>й</u> тннт 20 неенд	50 05 34 43 290 092	PHOH BIDA BIDA	
ACP - 1500C	K 0.05	DEC 0.1 HON 0.16	TKPEB 0.2 ARFSH 0.3 CNDTZ 0.4	KOZFT 0.5 PBHAD 0.4 RZCNB 0.7	VSHEL 0.8 APFCB 0.9 RDZTG 1.0	HKNST 1.2 OVEFG 1.5 DACZR 2.0
11, ¹² ,1 3 3 3 4 2 0 9 5 0 5 0 5 0 5 0 5 0 5 0 5 0 5 0 5 0 5 0 5 0 5 0 5 0 5 0 9 0 0 9 1 9 0 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	∃ШП 0.1 ПЕШ 0.2	EMBWE0.3 WEMBM0.4 EBWME0.6	3EWMW 0.6 W3ME3 0.7 MWE3M 0.8	3MEWE 1.0 MW3EM 1.2 WEM3E 1.6	458 % 293 %	54367 0,3 68294 0,4 32865 0,5
285630,6 945271.0 934270,7 683491.2 569840,8 592831.5	A 0.1	ि ै के 0.2 २ व्य के 0.3	2 * 2 & 2 0.4 2 # Ø f 2 0.5 Ø & 2 * # 0.5	* 1 X 5 1 0.7 = 1 2 * 1 0.8 1 5 = X 2 1.0	۲	0
	•		8	-		

Specifications

 Projection distance 	
---	--

- Projection magnification
- Projection size
- Chart
- Speed of chart conversion
- Mask
- Speed of mask conversion
- Program
- Light source
- Auto-off function
- Power source
- Power consumption
- Dimensions
- Net weight
- Accessories
- Optional accessories
- 1.5m ~ 6m 30 x (at 5m) 330mm(W) x270mm(H) (at 5m) 30 different pattern One chart per 0.01~0.02s 1 open, 5 horizontal lines, 8 vertical lines, 21 single letters, 1 red/green One mask per 0.03s 2 sets programs, each program contains up to 30 steps LED light After 10 minutes idle time. AC 220V, 50Hz or 110V, 60Hz 80W 300mm(L) x 230mm(W) x 240mm(H) 6Kg Remote control, Polarized metal screen, halogen lamp, polarized glasses, fuses(2), batteries(2) Floor stand, wall stand





MUSEUM HILL CENTRE, MUSEUM ROAD P.O. BOX 75534 00200 NAIROBI, KENYA Tel: 0720 714 337 Email: info@medsurgehealth.co.ke Web: www.medsurgehealth.co.ke

